




AquaPASS[®]

Phased Activated Sludge System

Mark P. Hughes, P.E.
Product Manager – Biological Processes






Presentation Outline

- Definition of the AquaPASS[®] System
- Process Description of the AquaPASS[®] System
- Applications
- Process Comparisons/Advantages
- Summary



What is an AquaPASS[®] System?

- **Phased Activated Sludge System**
- Continuous Flow, Activated Sludge
- Aqua MixAir[®] System
- Biological Nutrient Removal (BNR)
Focus





AQUA-AEROBIC SYSTEMS, INC.

Aqua MixAir[®] System



Aqua MixAir[®] System

Heart of Biological Systems

- Independent Mixing
 - AquaDDM[®] Mixer
 - AquaCAM-D[®]
- Independent Aeration
 - Diffused or surface aeration
 - Retrievable or fixed





Aqua MixAir® System Biological Nutrient Removal



Aerobic Mixing (Nitrification)




Anoxic Mixing
(Denitrification and Power Savings)




Aqua MixAir[®] System

Energy Control



“Significant power savings can be experienced with the Aqua MixAir[®] system”

“A 1 MGD plant could save \$10,000 in the first year with the Aqua MixAir[®] system and proportional D.O. control”





Supplemental Carbon Addition

Aiding Denitrification

- Review of 40 AquaSBR[®] installations with effluent TN requirement of 10 mg/l or less.
 - 12% additional carbon
- Literature review of 20 flow-through BNR plants designed for 10mg/l or less.
 - 65% add additional carbon



Supplemental Carbon Addition

Plant Name	Design Effluent TN (mg/l)	Carbon Addition	% of Design Load BOD	Design C:N Ratio	Current C:N Ratio (no Carbon)	Current C:N Ratio (w/ Carbon)	Carbon Added (lbs/day)
Big Coppitt, FL	3	No	19.9%	4.03	1.63	1.63	N/A
Boonsboro, MD	3	No	42.5%	4.76	4.01	4.01	N/A
Key Largo, FL	3	Yes	31.5%	5.00	4.69	4.90	86.7
Mashantucket, CT	3	No	17.9%	3.60	6.12	6.12	N/A
Millville, FL	3	No	60.2%	3.89	8.31	8.31	N/A
Huntington, NY	4	Yes	66.8%	4.50	4.03	4.20	104.1
Lee, MA	6	No	42.3%	5.80	6.48	6.48	N/A
Dale Service Section 1, VA	8	Yes	47.1%	4.41	4.00	4.71	891.7
Dale Service Section 8, VA	8	Yes	47.1%	4.41	4.00	5.03	1,288.0

C:N Ratio from 1.63-8.31 with and without carbon addition



Supplemental Carbon Addition

Flow-Through Systems

Plant Name	Design Effluent TN (mg/l)	Carbon Addition	Current C:N Ratio (no Carbon)	Current C:N Ratio (w/ Carbon)	Carbon Added (lbs/day)	Process
Alexandria Renew WRF, VA	3	Yes	5.5	7.8	12028.2	5 Stage Bardenpho
Central Johnston, NC	3.7	Yes	Unknown	10	Unknown	Activated Sludge with denite filter
Clark County, NV	5.8	No	5.5	5.50	N/A	A/O
Clearwater, FL	3	No	6.7	6.7	Unknown	Bardenpho
Crowders Creek WWTP	6	Yes	Unknown	Unknown	1200.0	A ² O
Easton WWTF, MD	4	Yes	Unknown	Unknown	62.8	Oxidation Ditches configured as 5 Stage Bardenpho
Elkton WWTF, MD	3.8	No	Unknown	Unknown	120.1	Oxidation Ditch with Post-Anoxic and Re-aeration tanks.
Henrico County, VA	5	Yes	Unknown	7.90	Unknown	5 Stage Bardenpho
JD Phillips, CO	10	Yes	Unknown	Unknown	5343.5	A ² O - 3 stage
Kalispell, MT	4	No	5.7	5.70	N/A	Modified UCT
Kelowna, BC	4.38	No	5.3	5.3	Unknown	Westbank
Lee County, FL	3	Yes	Unknown	4	Unknown	Activated Sludge with denite filter
Long Creek WWTP	6	Yes	Unknown	Unknown	1660.0	A ² O
Lott WWTP, WA	10	Yes	Unknown	4.75	3616.4	4 stage bardenpho
MWRD RWHTF, CO	10	Yes	Unknown	Unknown	10000.0	MLE
Neuse River WWTP, NC	2.7	Yes	Unknown	Unknown	8917.1	4 Stage Bardenpho with denite filters
Noman M. Cole PCP, VA	5.25	No	5.40	5.40	N/A	Step Feed Activated Sludge and denite filter
North Cary, NC	3.94	No	4.3	4.3	Unknown	Oxidation Ditch
TP Smith WRF, FL	3	Yes	Unknown	Unknown	8818.0	4 Stage Bardenpho
Western Branch WWTP, MD	3	Yes	Unknown	13.90	Unknown	4 anoxic, 8 aerobic reactors

C:N Ratio > 4 required to meet effluent TN limits



Aqua MixAir[®] System

Summary

- The Heart of Aqua-Aerobic Systems' Biological Process and Adaptive Design
- Advantages of Efficient Mixing
 - Process Control
 - Energy Savings
 - Carbon Savings
 - Improved Treatment (BNR) at Minimal Additional Cost




AquaPASS[®]

System Operation



AquaPASS[®] System Description





Step 1: Anaerobic Treatment



- Influent Combined With Thickened RAS
- D.O. = 0 mg/l & < 3 mg/l NO_x-N
- HRT 0.5 – 1.5 Hours
- Complete Mix
- Bio-P Release
- Selector Basin



Step 2: Staged Aeration




- Multi-Level Aeration Management
 - Aerobic and Anoxic Events
 - D.O Control



Step 3: Phase Separator


Phase Separator



- RAS from Final Clarifier
- Typical HRT 0.5 Hours
- RAS Concentrated 20% – 50%
- Supernatant Transferred to Staged Reactors
- Thickened Sludge to Pre-Anoxic Reactor



Step 4: Pre-anoxic Reactor




- Thickened RAS from Phase Separator
- Typical HRT 0.5 – 1.5 Hours
- $\text{NO}_3\text{-N}$ Reduced Prior to Anaerobic Reactor
- Internal Recycle Rates 15% – 30% of Influent Flow



AquaPASS[®] System


Process Flow





AquaPASS[®] System

Layout Example






AquaPASS[®]

Design Considerations



AquaPASS[®] System

SAR - Aerobic/Anoxic






AquaPASS[®] System

SAR - Aerobic/Anoxic ~15-18 hours HRT

Influent






Nutrient Control

Staged Aeration/Anoxic Reactor - Nitrogen Control

On/Off Management






AquaPASS[®]

System Components



AquaPASS[®] Components

Unequaled Quality



Aqua MixAir[®]



Phase Separator



Aqua-Aerobic Control Solutions



Phase Separator





Phase Separator



RAS from Clarifier



Return to Staged
Aeration Reactor





AquaPASS®

Installation Profiles



Installation Profile

Salisbury Township WWTP, PA - Retrofit



**Expansion of an existing activated sludge system
to meet new BNR requirements.**



Installation Profile

Salisbury Township WWTP, PA - Retrofit

Avg. Flow 0.58 MGD / Peak Flow 1.16 MGD			
Loading	Design Influent (mg/l)	Design Effluent (mg/l)	Avg. Effluent (mg/l)*
BOD	250	15	2.5
TSS	215	30	4.6
TKN	35	---	2.6
NH3-N	---	1	0.42
Total N	---	6.9	4.5
Total P	6	0.86	0.25

***Based on data from 01/2011 - 04/2012**



Summary



Summary

- Efficient “BNR” Performance
- Time-Management of Process (Flexibility)
- Proportional Aeration Turndown via Aqua MixAir[®] System
- Low Headloss (constant water level)
- Flexible Design
- **Low Life-Cycle Cost** (Mixing, Pumping, Aeration)



AquaPASS[®] Phase Activated Sludge System

Questions?

