



ADEX HP 30 FAST
Declaration of performance
N. CPR-IT2/0101

DECLARATION OF PERFORMANCE N. CPR-IT2/0101

- 1) Unique identification code of the product-type: **ADEX HP 30 FAST**
- 2) Intended uses: **Improved fast setting cementitious adhesive for internal and external tiling on floors and walls**
- 3) Manufacturer: **ADESITAL S.p.A. – Via XX Settembre 12/14, – 41042 Ubersetto di Fiorano (MO) – Italia - www.adesital.it**
- 4) Sistemi di VVCP: **System 3**
- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies: **The notified laboratory LGAI, Technological Center S.A./Applus, N. 0370 carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared::

Essential characteristics	Performances
Reaction to fire:	Class E
Bond strength, as:	
- initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
-early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Durability for:	
- tensile adhesion after heat ageing	$\geq 1,0 \text{ N/mm}^2$
- tensile adhesion after water immersion	$\geq 1,0 \text{ N/mm}^2$
- tensile adhesion after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by: **Marco Corradi – Managing Director**
Ubersetto di Fiorano (MO), 25/11/2019

DoP in Pdf format are available in the Adesital website.

Revision 0 notes: First issue

ADEX HP 30 FAST
CE MARKING
Annex to DoP N. CPR-IT2/0101



 0370	Adesital S.p.A. Via XX Settembre 12/14 – 41042 Ubersetto di Fiorano (MO) (Italy) www.adesital.it
19 CPR-IT2/0101 EN 12004 ADEX HP 30 FAST <i>Improved fast setting cementitious adhesive for internal and external tiling on floors and walls</i>	
Reaction to fire: Bond strength, as: - initial tensile adhesion strength -early tensile adhesion strength Durability for: - tensile adhesion after heat ageing - tensile adhesion after water immersion - tensile adhesion after freeze/thaw cycles Release of dangerous substances	Class E $\geq 1,0 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ See SDS

Note:

ADESITAL supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*