

**Specification of Sender:**

Model No.	MT-50T	
Transmission distance	50m	
Input resolution	1920*1440	
Input	VGA video	1 * VGA port
	Audio	1* 3.5mm audio
Output resistance	VGA video	75Ω
	Audio	5Ω
	VGA synchronize	4.7kΩ
Input level	VGA video	0.7Vp-p
	VGA synchronize	TTL
	Audio	0.75Vp-p
Output	1 Road rj45	
Local output/ expand output	1 group VGA + 3.5mm Audio	
Power port	USB power port( 5V)	

**Specification of receiver:**

Model No.	MT-50T	
Output resolution	1920*1400	
Input Rj45	1 road	
Output	VGA	2 road
	Audio	2 road
High frequency compensation	9 part 0±6db	
Gain compensation	1- 2	
Power port	DC 5V 1A	

**Features:**

Uses Cat5e/6 cable to connect the local and the remote units

Has anti-static, anti-lightning, anti - interference function

Transmission distance up to 50m

High-quality video – up to 1920\*1440@60Hz

Easy to use and supports all system

Supports VGA, SVGA, XGA, SXGA, UXGA, WUXGA and multisync monitors

Dual Audio/video

Supports one local and two remote displays

Audio enabled

Supports DDC for the local monitor