

grease equipment - battery operated

powergun™

"Winner – 2007 Australian Technology & Innovation Award by Power Torque Magazine"



Features

- continuous grease flow
- 762 mm (30") flexible extension for hard to reach areas
- quick 1 hour battery recharge
- up to 3 cartridges per charge
- includes carry case, battery charger and spare battery
- refillable by cartridge or bulk
- available in 400g and 450g models
- fully serviceable
- 10 year warranty and parts guarantee
 (12 months on battery and charger, 5 years on electric motor)

Accessories

- KZD Needlenose Coupler
- KZHY Hyperdermic Needlepoint Coupler
- KFR Rigid/Flexible Extension
- KSR/KGR Buttonhead Coupler

Specifications

- grease viscosity: up to NLGI No.2
- wetted components: aluminium, steel and nitrile rubber
- output:
 - 100 g /min (3.5 oz/min) free flow
- maximum pressure: 34 500 kPa (5 000 psi, 345 bar)
- minimum temp: 0°C (32°F)
- maximum temp: 50 °C (122 °F)
- battery voltage:12 V NiCad
- battery capacity: 1300 mAh
- est. output per battery charge: up to 3 cartridges

Head Office - Sydney
Macnaught Pty Ltd
41-49 Henderson St, Turrella
Sydney NSW 2205 Australia
P: +61-2-9567 0401
F: +61-2-9597 7773
E: info@macnaught.com.au
W: www.macnaught.com.au



Macnaught USA
Macnaught USA, Inc.
614 South Ware Boulevard
Dock 14A (for deliveries)
Tampa, FL 33619
P: 813-628-5506
F: 509-694-8495
E: info@macnaughtusa.com
W: www.macnaughtusa.com

Macnaught Europe
Macnaught Europe Ltd
D1 Lincoln Park
Borough Road
Buckingham Road Ind Est
Brackley NN13 7BE
United Kingdom
P: +44 1280 705001
F: +44 1280 705006
E: info@macnaughteurope.com
W: www.macnaughteurope.com

